

**ISSN 2518-170X (Online),
ISSN 2224-5278 (Print)**

ҚАЗАҚСТАН РЕСПУБЛИКАСЫ
ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

К. И. Сатпаев атындағы Қазақ ұлттық техникалық зерттеу университеті

Х А Б А Р Л А Р Ы

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК
РЕСПУБЛИКИ КАЗАХСТАН
Казахский национальный исследовательский
технический университет им. К. И. Сатпаева

NEWS

OF THE ACADEMY OF SCIENCES
OF THE REPUBLIC OF KAZAKHSTAN
Kazakh national research technical university
named after K. I. Satpayev

ГЕОЛОГИЯ ЖӘНЕ ТЕХНИКАЛЫҚ ҒЫЛЫМДАР СЕРИЯСЫ

◆ СЕРИЯ ГЕОЛОГИИ И ТЕХНИЧЕСКИХ НАУК

◆ SERIES OF GEOLOGY AND TECHNICAL SCIENCES

5 (431)

ҚЫРКҮЙЕК – ҚАЗАН 2018 ж.
СЕНТЯБРЬ – ОКТЯБРЬ 2018 г.
SEPTEMBER – OCTOBER 2018

ЖУРНАЛ 1940 ЖЫЛДАН ШЫГА БАСТАФАН
ЖУРНАЛ ИЗДАЕТСЯ С 1940 г.
THE JOURNAL WAS FOUNDED IN 1940.

ЖЫЛЫНА 6 РЕТ ШЫГАДЫ
ВЫХОДИТ 6 РАЗ В ГОД
PUBLISHED 6 TIMES A YEAR

NAS RK is pleased to announce that News of NAS RK. Series of geology and technical sciences scientific journal has been accepted for indexing in the Emerging Sources Citation Index, a new edition of Web of Science. Content in this index is under consideration by Clarivate Analytics to be accepted in the Science Citation Index Expanded, the Social Sciences Citation Index, and the Arts & Humanities Citation Index. The quality and depth of content Web of Science offers to researchers, authors, publishers, and institutions sets it apart from other research databases. The inclusion of News of NAS RK. Series of geology and technical sciences in the Emerging Sources Citation Index demonstrates our dedication to providing the most relevant and influential content of geology and engineering sciences to our community.

Қазақстан Республикасы Ұлттық ғылым академиясы "ҚР ҰҒА Хабарлары. Геология және техникалық ғылымдар сериясы" ғылыми журналының Web of Science-тің жаңаланған нұсқасы Emerging Sources Citation Index-те индекстелуге қабылданғанын хабарлайды. Бұл индекстелу барысында Clarivate Analytics компаниясы журналды одан әрі the Science Citation Index Expanded, the Social Sciences Citation Index және the Arts & Humanities Citation Index-ке қабылдау мәселесін қарастыруды. Web of Science зерттеушілер, авторлар, баспашилар мен мекемелерге контент тереңдігі мен сапасын ұсынады. ҚР ҰҒА Хабарлары. Геология және техникалық ғылымдар сериясы Emerging Sources Citation Index-ке енүі біздің қоғамдастық үшін ең өзекті және беделді геология және техникалық ғылымдар бойынша контентке адалдығымызды білдіреді.

НАН РК сообщает, что научный журнал «Известия НАН РК. Серия геологии и технических наук» был принят для индексирования в Emerging Sources Citation Index, обновленной версии Web of Science. Содержание в этом индексировании находится в стадии рассмотрения компанией Clarivate Analytics для дальнейшего принятия журнала в the Science Citation Index Expanded, the Social Sciences Citation Index и the Arts & Humanities Citation Index. Web of Science предлагает качество и глубину контента для исследователей, авторов, издателей и учреждений. Включение Известия НАН РК. Серия геологии и технических наук в Emerging Sources Citation Index демонстрирует нашу приверженность к наиболее актуальному и влиятельному контенту по геологии и техническим наукам для нашего сообщества.

Бас редакторы
э. ф. д., профессор, КР ҮГА академигі
И.К. Бейсембетов
Бас редакторының орынбасары
Жолтаев Г.Ж. проф., геол.-мин. ф. докторы
Редакция алқасы:

Абаканов Т.Д. проф. (Қазақстан)
Абишева З.С. проф., академик (Қазақстан)
Агабеков В.Е. академик (Беларусь)
Алиев Т. проф., академик (Әзірбайжан)
Бакиров А.Б. проф., (Қыргыстан)
Беспаев Х.А. проф. (Қазақстан)
Бишимбаев В.К. проф., академик (Қазақстан)
Буктуков Н.С. проф., академик (Қазақстан)
Булат А.Ф. проф., академик (Украина)
Ганиев И.Н. проф., академик (Тәжікстан)
Грэвис Р.М. проф. (АҚШ)
Ерғалиев Г.К. проф., академик (Қазақстан)
Жуков Н.М. проф. (Қазақстан)
Кенжалиев Б.К. проф. (Қазақстан)
Қожахметов С.М. проф., академик (Казахстан)
Конторович А.Э. проф., академик (Ресей)
Курскеев А.К. проф., академик (Қазақстан)
Курчавов А.М. проф., (Ресей)
Медеу А.Р. проф., академик (Қазақстан)
Мұхамеджанов М.А. проф., корр.-мүшесі (Қазақстан)
Нигматова С.А. проф. (Қазақстан)
Оздоев С.М. проф., академик (Қазақстан)
Постолатий В. проф., академик (Молдова)
Ракишев Б.Р. проф., академик (Қазақстан)
Сейтов Н.С. проф., корр.-мүшесі (Қазақстан)
Сейтмуратова Э.Ю. проф., корр.-мүшесі (Қазақстан)
Степанец В.Г. проф., (Германия)
Хамфери Дж.Д. проф. (АҚШ)
Штейнер М. проф. (Германия)

«ҚР ҮГА Хабарлары. Геология мен техникалық ғылымдар сериясы».

ISSN 2518-170X (Online),

ISSN 2224-5278 (Print)

Меншіктенуші: «Қазақстан Республикасының Ұлттық ғылым академиясы» РКБ (Алматы қ.).

Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрагат комитетінде 30.04.2010 ж. берілген №10892-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік.

Мерзімділігі: жылдан 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18,
<http://nauka-nanrk.kz/geology-technical.kz>

© Қазақстан Республикасының Ұлттық ғылым академиясы, 2018

Редакцияның Қазақстан, 050010, Алматы қ., Қабанбай батыра көш., 69а.

мекенжайы: Қ. И. Сәтбаев атындағы геология ғылымдар институты, 334 бөлме. Тел.: 291-59-38.

Типографияның мекенжайы: «Аруна» ЖҚ, Алматы қ., Муратбаева көш., 75.

Г л а в н ы й р е д а к т о р
д. э. н., профессор, академик НАН РК

И. К. Бейсембетов

Заместитель главного редактора

Жолтаев Г.Ж. проф., доктор геол.-мин. наук

Р е д а к ц и о н а я к о л л е г и я:

Абаканов Т.Д. проф. (Казахстан)
Абишева З.С. проф., академик (Казахстан)
Агабеков В.Е. академик (Беларусь)
Алиев Т. проф., академик (Азербайджан)
Бакиров А.Б. проф., (Кыргызстан)
Беспаев Х.А. проф. (Казахстан)
Бишимбаев В.К. проф., академик (Казахстан)
Буктуков Н.С. проф., академик (Казахстан)
Булат А.Ф. проф., академик (Украина)
Ганиев И.Н. проф., академик (Таджикистан)
Грэвис Р.М. проф. (США)
Ергалиев Г.К. проф., академик (Казахстан)
Жуков Н.М. проф. (Казахстан)
Кенжалиев Б.К. проф. (Казахстан)
Кожахметов С.М. проф., академик (Казахстан)
Конторович А.Э. проф., академик (Россия)
Курскеев А.К. проф., академик (Казахстан)
Курчавов А.М. проф., (Россия)
Медеу А.Р. проф., академик (Казахстан)
Мухамеджанов М.А. проф., чл.-корр. (Казахстан)
Нигматова С.А. проф. (Казахстан)
Оздоев С.М. проф., академик (Казахстан)
Постолатий В. проф., академик (Молдова)
Ракишев Б.Р. проф., академик (Казахстан)
Сейтов Н.С. проф., чл.-корр. (Казахстан)
Сейтмуратова Э.Ю. проф., чл.-корр. (Казахстан)
Степанец В.Г. проф., (Германия)
Хамфери Дж.Д. проф. (США)
Штейнер М. проф. (Германия)

«Известия НАН РК. Серия геологии и технических наук».

ISSN 2518-170X (Online),

ISSN 2224-5278 (Print)

Собственник: Республикаинское общественное объединение «Национальная академия наук Республики Казахстан (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №10892-Ж, выданное 30.04.2010 г.

Периодичность: 6 раз в год

Тираж: 300 экземпляров

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел.: 272-13-19, 272-13-18,
<http://nauka-nanrk.kz/geology-technical.kz>

© Национальная академия наук Республики Казахстан, 2018

Адрес редакции: Казахстан, 050010, г. Алматы, ул. Кабанбай батыра, 69а.

Институт геологических наук им. К. И. Сатпаева, комната 334. Тел.: 291-59-38.

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75

Editor in chief
doctor of Economics, professor, academician of NAS RK

I. K. Beisembetov

Deputy editor in chief

Zholtayev G.Zh. prof., dr. geol-min. sc.

Editorial board:

Abakanov T.D. prof. (Kazakhstan)
Abisheva Z.S. prof., academician (Kazakhstan)
Agabekov V.Ye. academician (Belarus)
Aliyev T. prof., academician (Azerbaijan)
Bakirov A.B. prof., (Kyrgyzstan)
Bespayev Kh.A. prof. (Kazakhstan)
Bishimbayev V.K. prof., academician (Kazakhstan)
Buktukov N.S. prof., academician (Kazakhstan)
Bulat A.F. prof., academician (Ukraine)
Ganiyev I.N. prof., academician (Tadzhikistan)
Gravis R.M. prof. (USA)
Yergaliев G.K. prof., academician (Kazakhstan)
Zhukov N.M. prof. (Kazakhstan)
Kenzhaliyev B.K. prof. (Kazakhstan)
Kozhakhetmetov S.M. prof., academician (Kazakhstan)
Kontorovich A.Ye. prof., academician (Russia)
Kurskeyev A.K. prof., academician (Kazakhstan)
Kurchavov A.M. prof., (Russia)
Medeu A.R. prof., academician (Kazakhstan)
Muhamedzhanov M.A. prof., corr. member. (Kazakhstan)
Nigmatova S.A. prof. (Kazakhstan)
Ozdoyev S.M. prof., academician (Kazakhstan)
Postolatii V. prof., academician (Moldova)
Rakishev B.R. prof., academician (Kazakhstan)
Seitov N.S. prof., corr. member. (Kazakhstan)
Seitmuratova Ye.U. prof., corr. member. (Kazakhstan)
Stepanets V.G. prof., (Germany)
Humphery G.D. prof. (USA)
Steiner M. prof. (Germany)

News of the National Academy of Sciences of the Republic of Kazakhstan. Series of geology and technology sciences.

ISSN 2518-170X (Online),

ISSN 2224-5278 (Print)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)

The certificate of registration of a periodic printed publication in the Committee of information and archives of the Ministry of culture and information of the Republic of Kazakhstan N 10892-Ж, issued 30.04.2010

Periodicity: 6 times a year

Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,
<http://nauka-namrk.kz/geology-technical.kz>

© National Academy of Sciences of the Republic of Kazakhstan, 2018

Editorial address: Institute of Geological Sciences named after K.I. Satpayev
69a, Kabanbai batyr str., of. 334, Almaty, 050010, Kazakhstan, tel.: 291-59-38.

Address of printing house: ST "Aruna", 75, Muratbayev str, Almaty

N E W S

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

SERIES OF GEOLOGY AND TECHNICAL SCIENCES

ISSN 2224-5278

<https://doi.org/10.32014/2018.2518-170X.19>

Volume 5, Number 431 (2018), 133 – 140

UDC 53.087.92

Khabai Anar¹, Zhi Wang², M. K. Baktybaev¹¹Kazakh National Technical Research University named after K. I. Satpaev, Almaty, Kazakhstan,²Zhejiang University, China.

E-mail: anar_kh@mail.ru, murat.baktybayev@gmail.com, wangzhi@iipc.zju.edu.cn

ANALYSIS OF THE SENSOR OF TEMPERATURE AND HUMIDITY MEASUREMENT BASED ON THE OPTICAL FIBER

Abstract. The intracavity sensitivity to humidity based on the optical fibers of the Fabry-Perot interferometer (FPI) was demonstrated by means of experiment. There was described the mechanism of tactile sensitivity of lasers and their parameters of sensitivity. There was also performed an analysis of fibers deformation depending on the temperature of the reverse reflection effect of fiber Bragg grating (FBG). Based on results of these analyses, there was offered the operational principle of optical fiber sensor, which measures the humidity and temperature.

Keywords: temperature and humidity sensor, Fabry-Perot interferometer, Fiber Bragg Grating, relative humidity, Single mode fiber.

Introduction. Humidity and temperature monitoring play a very important role in many technical and scientific fields such as chemistry, biology, meteorology, electronics, cars, plants, and production of microelectronics.

Nowadays, there are many digital sensors that use physical principles.

At the present time, there are sensors that measure the humidity and temperature in the unit [1-4]. The humidity and temperature sensor based on optical fibers have such qualities as high sensitivity, fast response, small in volume and electro-magnetic interference.

Different types of sensors based on crystal fiber used to determine humidity [5-8]. Methods for measuring the temperature of optical fibers were shown [10]. Measuring system based on sensitivity of optic fiber Bragg grating (OFBG) [10-13], Fabry-Perot interferometers (FPI) [14, 15], homogeneous optical fibers [16] were discussed in publications.

The consumption of Agarose gel is low and has good results in preparation and calculation. Therefore, it is often used for comparative humidity [17]. To improve the sensitivity of optical fibers, they are made of hygroscopic materials. For example, agarose gelgraphene oxide, polyvinyl alcohol, SiO₂, WS₂, and so on. In recent years, fiber-optic sensors based on intracavity sensing of optical fiberhave been investigated extensively because they can enhance the visibility of the resonant peak in the spectrum and narrow the 3 dB bandwidth [18-20].

In this article, given are experimental results of humidity that are based on fiber – optical analysis (FPI) with the range of 25 to 90 % as well as methods to determine temperature by reverse reflection of spectra on the basis of temperature dependence and optical fiber (Bragg grating).

1. Principle of the sensor's operation. Principle of thesensor's operation is based on two main sensitivities. First, it isdetermined by humidity sensitivity which is based on Fabry-Perot interferometer method. Second, determined optical fiber Bragg grating reflection effect of the strain change by temperature.

1.1. Spectrum reverses reflection effect of the optical Fiber Bragg Grating. It is called the Bragg wavelength (λ_B), and located in the middle of the waves which is the lumen of the filter to achieve the light spectrum that can satisfy the requirements of Bragg [3].

The value (λ_B) of these gratings in the most sensing temperature applications can be expressed as

$$\lambda_e = 2 \cdot \Lambda \cdot \eta_{eff} \quad (1)$$

where Λ is the spatial period of the Bragg grating, and η_{eff} is the effective refractive index of the optical single mode fiber. These two parameters are the function of strain and temperature. Optical Fiber Bragg Grating sensors (sensors shown in figure 2) are popular for detecting temperature strains. The Bragg wavelength shift ($\Delta\lambda_B$) induced by either a strain (ε) or temperature change (ΔT) is expressed by the following equation:

$$\frac{\Delta\lambda_e}{\lambda_e} = (1 - P_e) \cdot \varepsilon + [(1 - P_e) \cdot \alpha + \xi] \cdot \Delta T \quad (2)$$

Where respectively, P_e is the photoelastic constant, α is the thermal expansion coefficient, and ξ is the thermo optic coefficient of the optical single mode fiber.




Figure 1 – The image shows the lengths and the spatial periods of the gratings as well as the Bragg wavelengths at three different temperature values

Regarding the temperature monitoring, it is performed by using a commercial FBG sensor coated by acrylate, which is sensitive to this parameter as shown in Equations (1) and (2).

1.2. Based on the Fabry-Perot, interferometer is sensitive to humidity. The scheme of the humidity-sensitive FPI diagram is shown in figure 2. Bragg Grating is placed on Optic single mode fiber and its cross-section covered with a half-reflective film, which continues with vacuum cavity of the FPI. A silicone diaphragm covers the vacuum cavity of the FPI. In figure 2 the silicon diaphragm deposited with Agarose. There are two reflective surfaces which are front and back of the vacuum cavity, whose length defined as h . Due to occurrence of interference between these two surfaces, light reflects. Because of the thickness of the silicon diaphragm on the Agarose gel, both are much less than the length of the vacuum cavity. Agarose gel has been seen as one reflective surface in the theoretical model. Therefore, the total reflected electric fields E_r of the FPI. The FPI can have the reflected electric field of two pages as follows.

$$E_r = E_0 [\sqrt{R_1} + (1 - a)(1 - R_1)] \quad (3)$$

where E_0 is the input electric field, a is the transmission loss factors. R_1 and R_2 are the reflection coefficients of the two reflective surfaces. φ_{FPI} is the round-trip propagation phase shift, which can be given by

$$\varphi_{FP} = \frac{4\pi h}{\lambda} \quad (4)$$

Therefore, the peak wavelength of the m th order is given by

$$\lambda_m = \frac{2h}{m} \quad (5)$$

where m is an integer. We can derive the free spectral range, and the wavelength spacing between the two adjacent dips can be expressed as

$$\Delta\lambda_s = \frac{\lambda^2}{2h} \quad (6)$$

Total reflection spectra $I(\lambda)$ of the FPI is sensitive to humidity can be described as

$$f(\lambda) = \left| \frac{E_r}{E_0} \right|^2 = A + B \cos(2\varphi_{FR}) \quad (7)$$

Where

$$A = R_1 + (1 - a)^2(1 - R_1)^2 R_2, B = 2\sqrt{R_1 R_2}(1 - a)(1 - R_1) \quad (8)$$

According to Fresnel formula, the reflection coefficient of the agarose gel can be written as

$$R_2 = \left(\frac{n_A - 1}{n_A + 1} \right)^2 \quad (9)$$

where n_A is the refractive index of the Agarose. When the refractive index of Agarose changes, the reflectance at the second surface will change. Because the refractive index of agarose is sensitive to ambient humidity [15]. FPI can be used to determine the humidity content of the wavelength $I(\lambda)$ below.

$$f(\lambda) = R_1 + (1 - a)^2(1 - R_1)^2 \left(\frac{H\varepsilon_{A-1}}{H\varepsilon_A + 1} \right)^2 + 2\sqrt{R_1}(1 - a)(1 - R_1) \left(\frac{H\varepsilon_{A-1}}{H\varepsilon_A + 1} \right) \cos(2\varphi_{FP}) \quad (10)$$




Figure 2 – The scheme of fiber-optic sensor for measuring the temperature and humidity

2. Preparation of experimental equipment and analysis of results. The experimental setup of the sensitive humidity based on FPI defines the fiber Bragg grating sensitivity that depends on the temperature. Spectrum wavelength from optical fibrous source of the laser is 1500 nm. The gain medium of the fiber laser is the Erbium-doped fiber with the length of 3 meters. In the fiber ring cavity, there is an isolator, which controls unidirectional flow. The sensors are inserted in the fiber laser by a circulator and the transmission optical fiber (TOF, Thorlabs.). Vacuum cavity of FPI serves as a wavelength selective filter and is used as the sensing head for humidity detection. Optical spectrum analyzer (OSA, YOKOGAWA, AQ6370, spectral resolution 0.02 nm) connects the three output spectrum. There are two spectrum values alternately analyzed, where first spectrum reverses reflection effect of the optical Fiber Bragg Grating and second when the ambient humidity of the sensing head changes the power reflection of the FPI.




Figure 3 – Experimental setup;
Fiber optic laser light source, optical circulator, sensor, computer for results analysis, optical spectrometer analyzer

In the fabrication of the Fabry-Perot interferometer, the production of the silicon diaphragm employs mature micro-electromechanical system fabrication techniques, which provide capability of batch-production and we have reported that in [24]. The thickness of the silicon diaphragm is about $10 \mu\text{m}$ with dimension $2.5 \times 2.5 \text{ mm}$. The two reflecting surfaces are at the center in a vacuum environment. Then, the 2% Agarose gel deposited on the silicon diaphragm by a pipette. Agarose gel is prepared by dissolving the agarose powder in distilled water in the beaker. In the deposition process, the thickness of the Agarose is about $1 \mu\text{m}$.

In order to obtain the optimized SNR of the proposed humidity sensor, the sensor fabrication should ensure the spectral overlap between the peak in the spectrum of the FPI. In the experiments, the gain peak at about 1500 nm is selected for the intracavity sensing. The peak wavelength and the wavelength spacing of the FPI can be designed by changing the h length of the FP cavity. When the ambient humidity is 35 %RH, the reflection spectrum of the FPI is measured as in Fig. 4. In the reflection spectrum of the Fabry-Perot interferometer, the peak with maximum intensity is at about 1530 nm and the reflection loss is -12.2 dB. The wavelength of the FPI is 15.5 nm.




Figure 4 – The spectra of the Fabry-Perot interferometers and corresponding optical fiber when the ambient relative humidity is 35 %

Based on the FPI method, the relative humidity range is 20-98% RH. As the ambient humidity changes, the output spectra of the optical fiber laser is measured as shown in figure 5(a). Output power of the optical fiber laser increases from -36.78 to -22.61 dBm as the ambient humidity changes from 25 to 95 %RH with the resolution of 10 %RH. Accordingly, the signal-to-noise ratio increased from 30 to 45 dB and the transmittance was 3 dB, which was lower by 0.5 nm. The humidity sensitivity is measured to be 0.202 dB/%RH. It shows the sensor has a good linear response. The practice showed a good outline of the sensor. So, as the relative humidity of the environment has changed from 20 to 90%,., The agglomerate breakdown index is measured from 1.45 to 1.48 [23].




Figure 5 – The change in the optical fiber laser output spectrum when the ambient humidity varies from 20 to 90 %RH

Approximate response time of the sensor is as fast as of 72 ms. The recovery time is about 357 ms, which depends on the time of the humid air removed from the sensor. Input and remove time taken into consideration, the real response time and recovery time are shorter than the measured time.

Cross-sensitivity of the sensor is the laser spectrum of the fiber at any temperature. As the temperature increases from 25 to 45 °C, the release wavelength of the optical fiber laser sensor has a red shift from 1530.19 to 1530.64 nm and the output power decreases from -36.64 to -37.12 dBm. A low temperature cross sensitivity is receive as -0.025 dB/°C and 0.024 nm/°C.




Figure 6 – (a) Sensor response time of the sensor (b) Temperature cross-sensitivity of the fiber sensor, output spectra of the fiber laser as the ambient temperature increases from 25 to 44 °C

Output stability is an important parameter for internalfiber laser sensors, which limits their applications [14]. For the stability analysis of the fiber sensor, emission wavelength and output power has been measured over 180 minutes by fixed the humidity at 65 and 95 %RH, respectively. The optical fiber laser output spectrum is perspective shown in figure 7 (a) and 7 (b).Wavelength and power stability are analyzed in figure 7 (c). The standard diversions of wavelength and power fluctuation are 0.101 nm and 0.129 dBm respectively at 65 %RH, and the standard deviations are 0.046 nm and 0.137 dBm respectively at 95 %RH. It demonstrates that the sensor shows a good repeatability for its humidity response and the fluctuation of measured humidity value which is less than ± 2 percentage RH.




Figure 7 – The output spectrum of the optical fiber laser sensor by fixing the ambient relative humidity at (a) 65 %RH and (b) 95 %RH of the measured values measured in 180 minutes, and (c) the wavelength and power stability.

In response to the above results, we can control the temperature changes by determining the wavelengths of the fibrous fluid from wire mesh lattice sensitive to the temperature stages

Conclusion. In summary,based on the FPI method, theoretical substantiations were made and the results of the experiment on the sensitivity to humidity of agarose reflections were summed up. Also, a mathematical equation of optical fiber Bragg grating reflection effect of the strain change by temperature was created. We have suggested that the temperature can be determined on the basis of the reverse reflection spectrum according to the results, mentioned in the articles [10-13].

A compact humidity-sensitive optical fiber FPI was developed and inserted in a fiber laser for intracavity humidity sensing. We analyzed the sensing mechanism of the fiber laser sensor and characterized its sensing performance. The relative output power of the fiber laser had a good linear response to ambient humidity in a wide range from 25 to 90 %RH. In addition, the stability of the sensor was discussed.

The humidity and temperature sensor based on optical fibers have such qualities as high sensitivity, fast response, small in volume and electro-magnetic interference.

REFERENCES

- [1] Park S., Kang J., Park J. One-bodied humidity and temperature sensor having advanced linearity at low and high relative humidity range // Sensors and Actuators B 76 322–326 (2001).
- [2] Clemens Eder, Virgilio Valente, Nick Donaldson, Andreas Demosthenous. A CMOS Smart Temperature and Humidity Sensor with Combined Readout // 14, 17192-17211; doi:10.3390/s140917192 Sensors 2014.

- [3] Carlo Macaroni, Michele A., Caponero, Rosaria D., Amato, Daniela Lo Presti, Emiliano Schena. Fiber Bragg Grating Measuring System for Simultaneous Monitoring of Temperature and Humidity in Mechanical Ventilation // Sensors doi: 10.3390/s170407492 April 2017.
- [4] Williams R, Rankin N, Smith T., Galler D., Seakins P. Relationship between the humidity and temperature of inspired gas and the function of the airway mucosa // Crit. Care Med. 1996, 24, 1920–1929.
- [5] Wong W.C., Chan C.C., Chen L.H., Li T., Lee K.X., Leong K.C. Polyvinyl alcohol coated photonic crystal optical fiber sensor for humidity measurement // Sens. Actuator B. July 2012. Vol. 174. P. 563-569.
- [6] Huang C., Xie W., Yang M., Dai J., Zhang B. Optical Fiber Fabry–Perot Humidity Sensor Based on Porous Al₂O₃ Film // IEEE Photon. Technol. Lett. Oct. 2015. Vol. 27, N 20. P. 2127-2130,
- [7] Mathew J., Semenova Y., Farrell G. Effect of coating thickness on the sensitivity of a humidity sensor based on an Agarose coated photonic crystal fiber interferometer // Opt. Express. Mar. 2013. Vol. 21, N 5. P. 6313-6320.
- [8] Zhao C., Yuan Q., Fang L., Gan X., Zhao J. High-performance humidity sensor based on a polyvinyl alcohol-coated photonic crystal cavity // Opt. Lett. Dec. 2016. Vol. 41, N 23. P. 5515-5518.
- [9] Lagakos N., Bucaro J., Jarzynski J. Temperature-induced optical phase shifts in fibers // Appl. Opt. 1981. 20. P. 2305-2308.
- [10] Zhang W., Webb D.J., Peng G.-D. Investigation into Time Response of Polymer Fiber Bragg Grating Based Humidity Sensors // J. Lighthw. Technol. Apr. 2012. Vol. 30, N 8. P. 1090–1096.
- [11] Chen X., Zhang W., Liu C., Hong Y., Webb D.J. Enhancing the humidity response time of polymer optical fiber Bragg grating by using laser micromachining // Opt. Express. Oct. 2015. Vol. 23, N 20. P. 25942-25949.
- [12] Woyessa G., Nielsen K., Stefani A., Markos C., Bang O. Temperature insensitive hysteresis free highly sensitive polymer optical fiber Bragg grating humidity sensor // Opt. Express. Jan. 2016. Vol. 24, N 2. P. 1206-1213.
- [13] Massaroni C., Caponero M.A., R. D'Amato, Presti D.L., Schena E. Fiber Bragg Grating Measuring System for Simultaneous Monitoring of Temperature and Humidity in Mechanical Ventilation // Sensors. Apr. 2017. Vol. 17, N 4. P. 749.
- [14] Wang C., Zhou B., Jiang H., He S. Agarose Filled Fabry–Perot Cavity for Temperature Self-Calibration Humidity Sensing // IEEE Photon. Technol. Lett. Oct. 2016. Vol. 28, N 19. P. 2027-2030.
- [15] Pevec S., Donlagic D. Miniature all-silica fiber-optic sensor for simultaneous measurement of relative humidity and temperature // Opt. Lett. Dec. 2015. Vol. 40, N 23. P. 5646-5649.
- [16] Du B., Yang D., She X., Yuan Y., Mao D., Jiang Y., Lu F. MoS₂ based all-fiber humidity sensor for monitoring human breath with fast response and recovery // Sens. Actuators B. May 2017. Vol. 251. P. 180-184.
- [17] Barain C., Matias I.R., Arregui F.J., Lopez-Amo M. Optical fiber humidity sensor based on a tapered fiber coated with agarose gel // Sens. Actuators B Chem. 2000, 69, 127-131. doi:10.1016/S0925-4005(00)00524-4.
- [18] Liu Z., Tan Z., Yin B., Bai Y., Jian S. Refractive index sensing characterization of a singlemode-claddingless-singlemode fiber structure based fiber ring cavity laser // Opt. Express. Mar. 2014. Vol. 22, N 5. P. 5037-5042.
- [19] Bai X., Fan D., Wang S., Pu S., Zeng X. Strain sensor based on fiber ring cavity laser with photonic crystal fiber inline Mach-Zehnder interferometer // IEEE Photonics J. Aug. 2014. Vol. 6, N 4. P. 6801608.
- [20] Shi J., Wang Y., Xu D., Zhang H., Su G., Duan L., Yan C., Yan D., Fu S., Yao J. Temperature Sensor Based on Fiber Ring Laser With Sagnac Loop // IEEE Photon. Technol. Lett., Apr. 2016. Vol. 28, N 7. P. 794-797.
- [21] Zhang W., Webb D.J., Peng G.-D. Investigation into Time Response of Polymer Fiber Bragg Grating Based Humidity Sensors // J. Lighthw. Technol. Apr. 2012. Vol. 30, N 8. P. 1090-1096.
- [22] Liu T., Yin J., Jiang J., Liu K., Wang S., Zou S. Differential pressure-based fiber-optic temperature sensor using Fabry–Perot interferometry // Opt. Lett. Mar. 2015. Vol. 40, N 6. P. 1049-1052.
- [23] Gao R., Jiang Y., Ding W. Agarose gel filled temperature in sensitive photonic crystal fibers humidity sensor based on the tunable coupling ratio // Sens. Actuators B. Jan 2014. Vol. 195. P. 313-319.
- [24] Berruti G., Consales M., Borriello A., Giordano M., Buontempo S., Makovec A., Breglio G., Petagna P., Cusano A. A Comparative Study of Radiation-Tolerant Fiber Optic Sensors for Relative Humidity Monitoring in High-Radiation Environments at CERN // IEEE Photonics J. Dec. 2014. Vol. 6, N 6. P. 0601015.

Хабай Анар¹, Чжи Ван², М. К. Бактыбаев¹

¹К. И. Сәтбаев атындағы Қазақ ұлттық техникалық зерттеу университет, Алматы, Қазақстан,

²Чжэцзян университеті, Қытай

ОПТИКАЛЫҚ ТАЛШЫҚ НЕГІЗІНДЕ ТЕМПЕРАТУРА МЕН ЫЛГАЛДЫЛЫҚТА ӨЛШЕЙТИН ДАТЧИКТІ ТАЛДАУ

Аннотация. Ылгалдылықта байланысты Фабри-Перот интерферометрлері (ФПИ) негізінде оптикалық талшықтың ішкі сезімталдығы ұснылып, эксперименталды түрде көрсетілді. Лазерлік сенсорлық сезімтал механизмі және оның сезімталдық көрсеткіштегі сипаттады. Оптикалық талшықты брэгг торларының (ТБТ) белгілі бір спектірлік кері шағылысты эффектісіне негізделіп температураға талшықтың деформациялық өзге-

рісін талдау. Осы талдаулар негізінде температурамен ылғалдылықты бірлікте өлшейтін оптикалық талшықты датчиктің жұмысын ұсыну.

Түйін сөздер: температура мен ылғалдылық өлшейтін датчик, Фабри-Перот интерферометрлері, Оптикалық талшықты брэгг торларыны, салыстырмалы ылғалдылық, Бір бағтты талшық.

Хабай Анар¹, Чжи Ван², М. К. Бактыбаев¹

¹Казахского национального исследовательского технического университета им. К. И. Сатпаева,
Алматы, Казахстан,
²Университет Чжэцзян, Китай

АНАЛИЗ ДАТЧИКА ИЗМЕРЕНИЯ ТЕМПЕРАТУРЫ И ВЛАЖНОСТИ НА ОСНОВЕ ОПТИЧЕСКОГО ВОЛОКНА

Аннотация. Экспериментально продемонстрирована внутрирезонаторная чувствительность к влажности на основе оптических волокон интерферометров Фабри-Перо(ИФП). Описан механизм сенсорной чувствительности лазеров и их параметры чувствительности. Проведен анализ изменения деформации волокон в зависимости от температуры на обратном отражательном эффекте волоконной брэгговской решетки (ВБР). На основе этих анализов предложены принцип работы оптического волоконного датчика, который измеряет влажность и температуру.

Ключевые слова: датчик температуры и влажности, интерферометр Фабри-Перо, Брэгговская волоконная решетка, относительная влажность, однородное волокно.

Information of the authors:

Khabay Anar (anar_kh@mail.ru): 3rd year PhD student of The Kazakh National Technical Research University named after K. I. Satpaev (KazNTRU), Almaty, Kazakhstan, <https://orcid.org/0000-0002-0409-1531>

Ph.D. adviser: Baktybayev Murat Kyrgyzbayevich associate professor (murat.baktybayev@gmail.com); <https://orcid.org/0000-0001-5931-3149>

Overseas Ph.D. adviser: Zhi Wang associate professor of Zhejiang Universit, Republic of China.(wangzhi@iipc.zju.edu.cn)

**Publication Ethics and Publication Malpractice
in the journals of the National Academy of Sciences of the Republic of Kazakhstan**

For information on Ethics in publishing and Ethical guidelines for journal publication see <http://www.elsevier.com/publishingethics> and <http://www.elsevier.com/journal-authors/ethics>.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see <http://www.elsevier.com/postingpolicy>), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service <http://www.elsevier.com/editors/plagdetect>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайте:

www:nauka-nanrk.kz

ISSN 2518-170X (Online), ISSN 2224-5278 (Print)

<http://geolog-technical.kz/index.php/kz/>

Верстка Д. Н. Калкабековой

Подписано в печать 08.10.2018.

Формат 70x881/8. Бумага офсетная. Печать – ризограф.

15,0 п.л. Тираж 300. Заказ 5.